

## EV-2500AF

portable video presenter



- 1/3" 470,000 pixels IT CCD
- High quality 12x optical zoom plus 2x digital zoom
- Simple and easy to operate
- Auto focus
- Open stage for easy document movement
- Convenient rotating camera head and flexible lighting arms
- Nega/Posi conversion
- Colour/B&W selection

[EV2500AF leaflet -32.21k \(ev2500af\\_01.pdf\)](#)

### SPECIFICATIONS

Image pick-up element	1/3 " IT CCD
Total picture elements	795 (H) x 596 (V), 470,000
Effective picture elements	752 (H) x 582 (V)
Resolution (Video)	> 470 (H) x 380 (V)
Close-up lens	O
Optical zoom	12x
Digital zoom	2x (can be scrolled by remote controller)
Lens	3.8 - 70 mm, F=1,9-2,6
Focusing	Auto/Manual
Shooting area (Minimum)	16 x 12 mm
Shooting area (Maximum)	340 x 252 mm
Iris	Auto (with level adjustment)
White balance	Auto
Nega/Posi conversion	O
Colour/B&W selection	O
Gamma adjustment	----
Freeze function	----
On Screen Display (OSD)	----
Image rotation	----
Camera head rotation	O
Sync. system	Internal
Scrolling	O
Edge Enhancement	---
User pre-set	----
Input selection	----
C-Video input	----
S-Video input	----
Mic. input	----
Audio input	----
C-Video output	PAL
S-Video output	PAL
12VDC out terminal	O

<b>RS-232C control terminal</b>	DSUB 9 Pin
<b>USB terminal</b>	----
<b>Lighting unit</b>	Upper light
<b>Mouse</b>	----
<b>Wireless remote controller</b>	0
<b>Power source</b>	AC100-240 V, 50Hz
<b>Power consumption</b>	0,3-0,5 A
<b>Dimensions (WxDxH) mm</b>	706 x 403 x 575 (Set-up), 500 x 612 x 99 (Folded)
<b>Weight</b>	6 kg

Weight and Dimensions are approximate. Design and specifications are subject to change without prior notice.

---

ELMO EUROPE GMBH - Neanderstr. 18 - 40233 Duesseldorf - Germany  
Phone: ++49-211-386 47-0 / FAX: ++49-211-376 630 / E-Mail: info@elmoeurope.de